

2416 CROSSFIRE HOSE REEL

ONE POWERFUL ROTATING REEL YOU'RE GOING TO WANT IN YOUR FLEET'S ROTATION.

The 2416 Crossfire Hose Reel's large capacity allows you to hold 1.125 miles of 10" lay flat hose or 2 miles of 8" lay flat hose. The result? Enhanced efficiency by going further with a single piece of equipment.

- Carry more hose with less equipment
- Enhanced performance and efficiency
- Unparalleled safety features



FEATURES

HOSE REEL CAPACITY

The 2416 Crossfire takes hose capacity up a notch from our other hose reels, comfortably holding:

- 3 miles of 6" lay flat hose | 24, 660' sections
- 2.25 miles of 7.25" lay flat hose | 18, 660' sections
- 2 miles of 8" lay flat hose | 16, 660' sections
- 1.125 miles of 10" lay flat hose | 9, 660' sections

STANDARD WITH DUAL CHAIN DRIVE

Unleash unmatched performance, power, and efficiency with a dual chain drive. The 2416 Crossfire hose reel has a dual chain drive powered by [2] 1000cc hydraulic motors, able to fully utilize 60 GPM hydraulic flow from the tractor. The #100 HD roller chain and sprockets are precisely engineered to maximize pulling power without compromising reel speed.

120° OF REEL ROTATION

This lay flat hose reel can rotate 120° above its axles from 'travel' to 'work' mode while fully loaded, utilizing a heavy-duty slewing ring for smooth, consistent rotation. This Reel sits higher off the ground than our level-wind and pivoting solutions, improving the line of sight from the tractor cab for confident and precise hose placement onto the Reel.



SPECIFICATIONS

STANDARD

- Maximum Weight Rating: 50,000 lbs.
- Hose Reel Weight (Empty): 16,500 lbs.
- Length: 26' 10"
- Width: 11' 6"
- Approximate Height: 13' 6"
- [4] 700 Series 50-22.5 16-Ply Flotation Tires
- [2] 25,000 lbs. Tandem Spring Axles
- Front Combo Clevis Hitch
- Rear Hitch Ready with Trailer Plug Wiring
- [2] 22" Rear-Facing LED Light Bar
- Front and Rear Storage Basket
- Slew Bearing Turn-Table Rotation
- 12,000 lbs. Manual Tongue Jack with Spring-Loaded Foot
- Full-Width Fenders with Built-In Rear Steps
- 3" Thick Reel Side Walls
- DOT Lighting with Rear Flashers

OPTIONS

- Quantum Drive System Driven - Dual Motors
- 20,000 lbs. Electric Over Hydraulic Tongue Jack
- 20,000 lbs. Hydraulic Straight-to-Tractor Tongue Jack
- Hydraulic Brakes | Rear Axle
- Electric Over Hydraulic Brakes | Rear Axle
- Camera Package | [2] Night Vision Cameras and 7" In-Cab Monitor
- Front Pintle Hitch
- Front Bull-Pull Hitch
- Rear Pintle Hook | 60K GVW Capacity
- QDS Wireless Remote | Wind, Unwind, Freewheel
- QDS Wireless Remote Enhanced | Includes PN 600-000 + Pivoting Controls

