

DIETRICH 3-POINT TOOLBAR



BUILT TOUGH.

Reliable and effective for both high and low application rates, this toolbar is ready to tackle any job. Featuring Dietrich Series 70 shanks and 8" chisel sweeps, you get a higher rate of liquid manure application. That's what we call working smarter, not harder.

- Widths from 15' - 35'
- Dietrich sweep spacing from 24" to 30"
- GPA rates from 2,500 - 20,000+

FEATURES

BIG APPLICATION RATES. EVEN BIGGER PERFORMANCE.

Chisel sweeps are incorporated along the heavy-duty toolbar for application rates of 2,500 – 20,000+ gallons per acre (GPA). With 8" and 12" chisel sweeps available on this 3-Point bar, you have the options you need to get the job done to your liking.

ADJUSTABLE GAUGE WHEELS

The adjustable gauge wheels allow for various sweep and chisel height adjustment options. The result? Consistent liquid manure placement. Featuring our depth stop feature ensuring the chisel sweeps won't dig into the ground too deep.

ACCESSIBLE FLUX MANIFOLD

The flux manifold ensures consistent and precise manure flow distribution throughout the system. The flux manifold's hydraulic gate valve can be opened to clean out the manifold on the go without leaving the tractor cab, or if you are outside the cab, you can easily access and clean out the blockage.

DIETRICH 3-POINT TOOLBAR

SPECIFICATIONS

STANDARD

- 6" Flux manifold
- 8" low rate chisel sweep
- 2,500 – 6,000 GPA
- Lifts soil less than 1"
- Series 70 Dietrich Shank with spring trip
- Adjustable gauge wheels
- 6" swing arm with sweeping 90° elbows
- 6" pipe swivel
- 6" hose swivel
- 6" Krohne Flowmeter
- Pig discharge
- Standard pinch drop tube
- DOT lighting

UPGRADES

- 8" high rate chisel sweep
- 5,000 – 10,000 GPA
- Lifts soil less than 1.25"
- 12" high rate chisel sweep
- 10,000 – 15,000 GPA
- Lifts soil less than 1.25"
- 12" max lift chisel sweep
- 20,000+ GPA
- Winged drop tube for 2.5" Bumblebee hose
- Winged drop tube for 3" Bumblebee hose

