

GROUND TRACKER TANK BAR

INDUSTRY LEADER. FIELD CONTOUR FOLLOWER.

The Ground Tracker liquid manure injection tank bar boasts heavy-duty durability and innovative design, allowing you to easily and closely follow ground contours. Featuring swivel-mounted Phantom injection units, each swivel mount floats 30° in each direction for unmatched performance.

- Coverage Widths from 15' - 20'
- Phantom unit spacing from 24" to 30"
- Compatible with Phantom injection units
- Optional Timed Tank Manifold
- Swivel-Mounted Phantom Units



FEATURES

SWIVEL-MOUNTED PHANTOM INJECTION UNITS ENSURE CONSISTENT COVERAGE

Equipped with two swivel-mounted Phantom Injection Units spaced 24" or 30" apart, you're able to thoroughly cover your field even in rougher terrain. The mounts can swivel 30° in each direction to track contours without sacrificing top-notch injection performance.

GPA RATES FROM 2,500 — 20,000

The Phantom unit can handle a variety of liquid manure rates and achieve thorough coverage. The Phantom units are mounted on a 4.5° mounting plate and are rated for up to 12 MPH.

SECURE HYDRAULIC TRAVEL LOCKS

Locked, loaded and ready to ride. The hydraulic travel locks are sequenced with the wing fold cylinders for ease of operation and allow the swivels to remain in place in transport.

LOW-MOUNTED HYDRAULIC TANK MANIFOLD

The timed manifold evenly distributes liquid manure across the tank bar as it's being applied throughout the field. The manifold sits low on the tank, which makes it easier and safer to maintain and clean out whether it be on the job, or at the end of a season.

SPECIFICATIONS

STANDARD

- Weight is model specific
- Travel width is model specific
- 3/8" thick 6" x 4" steel mount tubes
- 2.5" diameter nickel-plated, steel swivel pins
- Phantom Unit swivel mounts (2 units per mount)
- Steel hose holders (1 per swivel mount)
- Internal grease grooves throughout the design
- Dual, counterbalance valves on wing cylinders
- Heavy-duty hydraulic row unit lock cylinders
- Timed tank manifold 8 and 10 manifold port options
- Tank plumbing
- 2.5" Bumblebee Hose and clamps
- 3" Bumblebee Hose and clamps
- Phantom Units
- Phantom Edge Units

