

HOSE HUSTLER



SAVE WEAR AND TEAR. SAVE TIME.

Taking care of your hose means taking care of your entire setup. Enter the Hose Hustler: the no-nonsense, smart solution. Using the Hose Hustler reduces the tension between the applicator and the hose laid out in the field, extending the life of your hose. Not only that, it minimizes the need to shut down while moving to a new quadrant in the field. Time is money, after all.

- Accomplish more in less time
- Increase the life of your lay flat hose
- Increase flexibility of lay flat hose positioning

FEATURES

OPTIMAL FIELD SET-UP WITH SIDE-SHIFT TECHNOLOGY

Featuring our exclusive side-shift technology, our Hose Hustlers have the ability to shift horizontally to one side. This allows you to effectively maneuver hose around obstacles throughout the field. Now, you can easily and more efficiently move hose by having the ability to 'side-shift' and drive or back down the entire line vs. driving into and back out of the line multiple times.

REDUCED HOSE TWISTING

Using a Hose Hustler reduces twisting by orienting your hose in the same direction that your applicator is traveling. A Hose Hustler also helps reduce hose rolling during crossovers and set changes. In the end? It saves you time and a whole lot of frustration.

MOUNT OPTIONS

The Hose Hustler is 3-point mounted and can be attached to the front or rear of the tractor allowing you to find the best setup for your operation.

HOSE HUSTLER

SPECIFICATIONS

STANDARD

ALL MODELS INCLUDE

- 3-point hitch mount | CAT 2, 3, and 4N compatible
- Heavy-duty hydraulic reel lock
- 3/8" thick 5X5 tube arms
- 1/2" side plate reinforcements

6" – 8" HOSE HUSTLER

- Reel frame is ideal for 6" & 8" lay flat hose
- 12,000 lb. hub & spindle
- Transport height – 11'
- Total length – 13'
- Clearance from hitch to reel – 6'
- Reel OD – 80"
- Reel ID – 60"
- Reel ID height – 13"

8" – 10" HOSE HUSTLER

- Reel frame is ideal for 8" & 10" lay flat hose
- 12,000 lb. hub & spindle
- Transport height – 12'
- Total length – 14'
- Clearance from hitch to reel – 5'
- Reel OD – 110"
- Reel ID – 84"
- Reel ID height – 14"

12" HOSE HUSTLER

- Reel frame is ideal for 12" lay flat hose
- 15,000 lb. hub & spindle
- Reinforcing reel gussets
- Transport height – 12'
- Total length – 14'
- Clearance from hitch to reel – 5'
- Reel OD – 110"
- Reel ID – 83"
- Reel ID height – 17"

UPGRADES

- Side-shift technology

