

QUICK ATTACH DRIBBLE TANK BAR

TOP-OF-THE-LINE SOLUTION TO TOP-SPREAD YOUR LIQUID MANURE.

Meet the Quick Attach Dribble Tank Bar. This applicator was built tough with thick steel tubing and a low-mounted Flux manifold allowing equal distribution of liquid manure across 44' sections of the field with each pass.

- Coverage Width of 44'
- 12" Dribble Line Spacing
- GPA Rates from 3,000 - 20,000+
- Narrow Folding Functionality
- Standard with a Flux Manifold
- Requires a Quick Attach H-Frame Tank Mount



FEATURES

GPA RATES FROM 3,000 — 20,000+

Dribble lines directly place liquid manure in contact with the ground, allowing operators to pump anywhere from 3,000 – 20,000+ gallons per acre through dribble lines that are spaced one foot apart from one another across a 44' wide tank bar.

ACCESSIBLE FLUX MANIFOLD

The flux manifold ensures consistent and precise manure flow distribution throughout the system. The flux manifold's hydraulic gate valve can be opened to clean out the manifold on the go without leaving the tractor cab, or if you are outside the cab, you can easily access and clean out the blockage.

IT'S JUST THAT - QUICK (ATTACH)

The Quick Attach (QA) Phantom Tank Bar is a great solution for applicators who want to quickly remove the bar from their liquid manure tank. Slim to no tools are required to make the transition, which means there's nothing slowing you down when it's go-time, time to clean or store your tank bar.

NARROW TRANSPORT WIDTH

13' 2" travel width. This is very narrow considering this tank bar has an application width of 44'. The way this dribble tank bar folds is the reason the travel width is so narrow and stows close to the liquid manure tank during travel.



SPECIFICATIONS

STANDARD

Weight:

- Bar & Flux manifold | 4,100 lbs.
- H-Frame tank mount | 700 lbs.
- Houle plumbing | 225 lbs.
- Travel width | 13' 2"

- 6" Flux Manifold
- 6" rear gate valve
- Manifold lid lift assist handle
- 6" tank to manifold plumbing
- 2.5" bumblebee hose Steel hose holders
- H-frame tank mount (Sold Separately)
- 3" bore hydraulic wing cylinders
- Greasable hinge tubes
- Dual, counterbalance valves on wing cylinders
- Bulkhead plates and quick attach hydraulic fittings

