

TOWABLE SPLASH BAR



JUST HITCH AND GO.

The 3-Point Towable Splash Bar is a quick liquid manure management solution. This dragline-style applicator can be used on a variety of field types. Use this bar to apply liquid manure or water irrigation on no-till ground, tilled ground, hay ground, alfalfa ground...we think you get the picture.

The 3-Point Towable Splash Bar is a cost-effective, simple solution for surface-applying liquid and easily towing to the next site with virtually any tow vehicle. This dragline-style applicator is low-weight, low-cost and works on a variety of field types to apply liquid on no-till, tilled, hay and/or alfalfa ground. Dominate a variety of field types, any day.

SPECIFICATIONS

STANDARD | ALL MODELS

- Splash pan discharge | Two splash patterns
- 6" Z-Swing arm
- 6" Rigid Hose Connection

STANDARD | FLOWMETER MODEL

- Manual gate valves

UPGRADES

- 6" Krohne Flowmeter
- Pipe swivel adder & swing arm updates
- Manual gate valves
- Hydraulic gate valves
- Hydraulic pig discharge

TOWABLE SPLASH BAR

SPECIFICATIONS

STANDARD

- 4414NHTB Cornell Pump
 - 150 HP tractor is recommended for 4414T booster pumps

UPGRADES

- 4NHTB Cornell Pump
- White iron components of 4517 Cornell Pump
- 250 HP tractor recommended for 4NHTB & 4517MP booster pumps
- Higher volume, 10STX Cornell Pump
- Pig launcher and or bypass