

1810 PIVOTING HOSE REEL

MORE REACTIVE. MORE PRODUCTIVE.

The 1810 Pivoting Hose Reel, with Chain Drive or Quantum Drive System (QDS) technology, quickly pivots at high speeds with precision, control and the right amount of torque for a tight wrap, every time. With fast site setup and even faster teardown, you'll be wondering how you ever got by without one in your equipment fleet.

- Highly maneuverable
- Reactive pivoting function
- Quick set-up and teardown time
- Low maintenance



FEATURES

HOSE REEL CAPACITY

The 1810 Pivoting Hose Reel comfortably holds the following lengths of lay flat liquid manure transfer hose:

- 2.25 miles of 6" lay flat hose | 18, 660' sections
- 1.5 miles of 7.25" lay flat hose | 12, 660' sections
- 1.25 miles of 8" lay flat hose | 10, 660' sections
- .75 miles of 10" lay flat hose | 6, 660' sections

COMPATIBLE WITH QUANTUM DRIVE SYSTEM TECHNOLOGY

QDS is the only three-speed hydraulic control on the market. This innovative system combines high-speed technology and precise control to wind and unwind hose as quickly as possible.

SINGLE AXLE FLOTATION TIRES

The dual 700 series/50 – 22.5 16-ply flotation tires give the reel a sturdy stance to wind and unwind hose while also reducing compaction.



1810 PIVOTING HOSE REEL

SPECIFICATIONS

STANDARD

- Length: 18' 1"
- Width: 13' 1.25"
- Approximate Height: 12' 1"
- Gross Weight (empty): 7,500 lbs.
- Maximum Weight Rating: 25,000 lbs.
- Single Motor, Heavy-Duty Double 80 Chain
- [2] 700 Series 50-22.5 flotation tires
- 25,000 lb. single-leaf spring axle
- Rear receiver hitch
- Front Combo clevis hitch
- [2] Rear-facing LED flood lights
- Front Frame Incorporated Storage Basket

OPTIONS

- Quantum Drive System Technology | Single motor
- QDS Wireless Remote | Includes wind, unwind, and freewheel
- Enhanced QDS Wireless Remote | Includes all functions of original, as well as, pivoting controls
- Camera package | Includes (2) night vision cameras and 7" in-cab monitor
- Hydraulic brakes
- Front Pintle Hitch
- Fenders

