

PHANTOM 1 INJECTION UNIT



PRECISE AND POWERFUL LIQUID MANURE INJECTION.

The Phantom Injector is an innovative liquid manure injector that treads so precisely in the field, it practically leaves no trace. With no additional tillage required, it delivers minimal soil disturbance while boasting maximum performance. These 7-horsepower units achieve consistent nutrient coverage throughout the field with precise nutrient injection, placing liquid manure 4"-6" below grade. It's environmentally smart. It's extremely precise. It's ready to get to work.

- Low soil disturbance
- Improved useful life
- Eliminates clogging
- Reduced streaking throughout the field
- Higher application rates
- Even nutrient coverage
- Precise nutrient placement
- No additional tillage required
- The spacing of our Phantom Units provide an advantage of their own

FEATURES

UP TO 15,000 GPA CAPABILITY

Phantom units can achieve GPA rates from 2,500 to 15,000. GPA rates will be dependent on unit spacing, ground conditions, type of liquid manure, etc.

COMPATIBLE WITH MULTIPLE PRODUCT LINES

The Phantom Injector is compatible with Bazooka's toolbars and tank bars, with convenient spacing options as narrow as 16".

13-WAVE CLOSURE BLADE

This helps with the Phantoms' ability to seal the liquid manure into the ground and reduces the amount of liquid manure discharged above ground, resulting in greater nutrient absorption and odor control.

SIMPLIFIED MAINTENANCE, INCREASED UPTIME

The Phantom Injector includes corrosion-resistant nickel plated pins and quick-change hubs and spindles for quick and easy maintenance.

PHANTOM 1 INJECTION UNIT

SPECIFICATIONS

STANDARD

Spacing Options:

- 16" Toolbars-Only
- 18" Toolbars-Only
- 20" Toolbars/ Tank Bars
- 24" Toolbars / Tank Bars
- 30" Toolbars / Tank Bars
- 4" – 6" Running Depth
- 6° Unit Angle – Recommended For Toolbars
- 4.5° Unit Angle – Recommended For Tank Bars
- Wavy, Main Coulter Blade | 22" Diameter
- Wavy, Closure Blade | 17" Diameter
- Depth Gauge Wheel And Cover Plate
- Mounting Plate
- Mild Steel Main Arm

- Cast Ductile Iron Closure Mount And Arm
- Nickel-Plated Mount Pin W/ Hardened Steel Bushings
- Bolt-In Main Hub And Spindle
- Adjustable Closure Blade Angle
- Adjustable Down-Force Spring
- 3" Drop Tube
- U-Bolts
- Assembly Hardware

UPGRADES

- Bolt-On Closure Spring Mount Plate

