

# QUICK ATTACH PHANTOM TANK BAR

## PRECISE, POWERFUL AND EFFICIENT LIQUID MANURE INJECTION.

The Quick Attach Phantom Tank Bar is a convenient, two-in-one liquid manure management solution. Now, switching between tank and dragline applications is a total breeze, and with reduced odor thanks to precision injection, it's a breeze worthy of taking a big ole whiff.

- Coverage Widths from 16' - 25'
- Phantom unit spacing from 20" to 30"
- Compatible with Phantom 1 and Phantom Edge injection units
- Folding Functionality
- Standard with an H-Frame Tank Mount



## FEATURES

### GPA RATES FROM 2,500 — 15,000

This unit can handle a variety of gallons per acre (GPA), adding versatility to its performance. It can achieve rates from 2,500 up to 15,000 while always delivering thorough coverage throughout the field.

### ACCESSIBLE FLUX MANIFOLD

The flux manifold ensures consistent and precise manure flow distribution throughout the system. The flux manifold's hydraulic gate valve can be opened to clean out the manifold on the go without leaving the tractor cab, or if you are outside the cab, you can easily access and clean out the blockage.

### IT'S JUST THAT - QUICK (ATTACH)

The Quick Attach Phantom Tank Bar is a great solution for applicators who want to quickly remove the bar from their liquid manure tank. Slim to no tools are required to make the transition, which means there's nothing slowing you down when it's go-time, time to clean or store your tank bar.

### 3-POINT UPGRADE OPTION

In a matter of minutes, an operation can be transformed from a tank to dragline application (and visa versa). A quick operational turnaround has been made possible with a QA Series universal attachment for both application methods.



# QUICK ATTACH PHANTOM TANK BAR

## SPECIFICATIONS

### STANDARD

Weight (without Phantom units):

- Bar & Flux manifold: Approximately 2,225 lbs. for models with coverage widths of 13-16'
- Bar & Flux manifold: Approximately 2,675 lbs. for models with coverage widths of 20-25'
- H-Frame tank mount | 700 lbs.
- Houle plumbing | 225 lbs.
- Add 270 lbs to the bar, manifold, frame mount and Houle plumbing total for each Phantom unit

Travel width:

- Approximately 13' for models with coverage widths of 16'
- Approximately 14' 6" for models with coverage widths of 20-25'

- 6" Flux Manifold
- 6" rear gate valve
- Manifold lid lift assist handle
- 6" tank to manifold plumbing
- 3" bumblebee hose
- Steel hose holders
- H-frame tank mount
- Heavy-duty hydraulic wing lock cylinders
- Large, hydraulic ram lock pins
- 4" bore hydraulic wing cylinders
- Greasable hinge tubes
- Internal, spiral grease grooves
- Bulkhead plates and quick attach hydraulic fittings
- Dual, counterbalance valves on wing cylinders

