

STANDARD FLEX TOOLBAR



SAVE ON ORGANIC NUTRIENTS AND COST.

A toolbar that derived from a solution that has been tested and proven for years, the rugged, Standard Flex Toolbar brings efficiency and environmental responsibility to the application process by utilizing a Phantom injection unit to inject liquid manure and lock in nutrients.

- Widths from 26' - 36'
- Phantom unit spacing from 16" to 30"
- GPA Rates from 2,500 - 20,000+
- Compatible with Phantom Edge injection units
- Ability to inject liquid manure around turns
- Switch between a 3-Point or Pull-Type application using one core toolbar
- Vertical folding toolbar design

FEATURES

REMOVABLE PULL-TYPE TONGUE

The pull-type tongue on the Flex is removable, allowing end-users the ability to mount the same bar on a 3-point hitch in a matter of minutes.

IDEAL FOR A VARIETY OF OPERATORS

With the ability to apply 2,500-20,000+ gallons per acre (GPA), the Standard Flex Toolbar equipped with Phantom units is a solid liquid manure injection solution for a variety of operations. Featuring shorter widths paired with Bazooka's trademark in-ground turns, it gives you a straightforward solution that delivers performance and cost savings.

ACCESSIBLE FLUX MANIFOLD

The flux manifold ensures consistent and precise manure flow distribution throughout the system. The flux manifold's hydraulic gate valve can be opened to clean out the manifold on the go without leaving the tractor cab, or if you are outside the cab, you can easily access and clean out the blockage.

SPECIFICATIONS

STANDARD

- Removable tongue with hydraulic and electrical quick connectors
- Phantom units on 6° mounting plates
- 6" Flux Manifold
- 6" swing arm with sweeping 90° elbows
- 6" pipe swivel
- 6" hose swivel
- 6" Krohne Flowmeter with cables
- DOT lighting
- Stainless steel knife gate valves
- 2.5" Bumblebee drop tube hoses
- Pig and main indicator lights
- [4] 12-16.5, 14 ply 8-8 center section tires
- CAT 4 bull pull hitch

UPGRADES

- 3" Bumblebee hose
- [2] 381 radial 12-16.5, 14 ply 8-8 hydraulic wing-gauge wheel tires
- [4] 381 radial 12-16.5, 14 ply 8-8 center section flotation tires
- John Deere Harvest Lab 3000 Swing Arm Mount Extension
- Phantom Edge injection units

- CAT 5 bull pull hitch
- 8" Upgrade | 8" Plumbing, 8" Swing Arm with Sweeping 90° Elbows, 8" Pipe Swivel, 8" to 6" Hose Swivel, and a 8" Krohne Flowmeter with Cables

6" HIGH-PERFORMANCE PACKAGE

- Manifold clog indicator light
- [4] 381 radial center section flotation tires
- Automatic grease system

8" HIGH-PERFORMANCE PACKAGE

- Manifold clog indicator light
- [4] 381 radial center section flotation tires
- Automatic grease system
- 8" Flux manifold
- 8" swing arm with sweeping 90° elbows
- 8" plumbing
- 8" Krohne Flowmeter with cables
- 8" pipe swivel
- 8" to 6" hose swivel

