

DRIBBLE BAR 2



GET UNDER THE CANOPY WITH YOUR MANURE APPLICATION

- Heavy-duty construction
- Easier to use
- Uniform distribution
- Reduce crop burn
- Reduce odor

Bazooka Farmstar's Dribble Bar 2 features serious enhancements from our original Dribble Bar. With our latest upgrades, this toolbar offers exceptional durability, precision, and efficiency, making it the perfect addition to your pumping operation. Avoid crop burn by placing the manure where you want it, right on the soil.



FEATURES

HIGH APPLICATION RANGE INCREASES PRODUCTIVITY

Dribble lines place liquid manure directly in contact with the ground. The Dribble Bar allows operators to apply anywhere from 3,000 – 25,000+ gallons per acre through the dribble lines spaced one foot apart.

ROBUST CONSTRUCTION

Let's talk about durability. The Dribble Bar 2 was designed to withstand anything you can throw at it - from rocky, uneven terrain to heavy use - this tool will take it all in stride.

HYDRAULIC, REAR FOLDING WINGS

The design of Dribble Bar 2 enables faster entry and exit from fields and safer travel between job sites, thanks to its narrow transport width.

ACCESSIBLE FLUX MANIFOLD

The flux manifold ensures consistent and precise manure flow distribution throughout the system. The flux manifold's hydraulic gate valve can be opened to clean out the manifold on the go, or if you are outside the cab, you can easily access and clean out the blockage.

Y-SHAPED DROP TUBES AND UPGRADED BUMBLEBEE HOSE

3-inch Bubblebee hose and Y-shaped drop tubes with a 3"-diameter, 3' long lay flat hose on the Dribble Bar 2 allows for easier flow of manure and reduces the risk of clogging.

WWW.BAZOOKAFARMSTAR.COM

DRIBBLE BAR 2

SPECIFICATIONS

STANDARD

- Coverage Widths: 44'
- Travel Width – Approximately 13' 6"
- Travel Length – Approximately 14'
- Weight – Approximately 5500 lbs
- 6" Flux manifold
- Rear hydraulic gate valve plumbing discharge to thoroughly purge & flush the system
- 6" Z-swing arm with a 6" hose swivel
- 6" plumbing and valves
- Hydraulic wing fold functionality
- Y-Shaped ports with two outlets, 12" apart
- 3" Bumblebee hose
- 3-Point standard hitch and compatible with quick hitch

UPGRADES

- Pipe Swivel: Swing arm style changes to accommodate a pipe swivel and a hose swivel, allowing easier turning.
- Flow meter: 6" Krohne Flowmeter with [2] 24' cables

