

42' OUTLAW FORCE-FEED TRAILER

PUMP OVER 4,000 GPM

The Outlaw Pump Trailer is a high-performance unit that offers increased efficiency and productivity. The 42' Outlaw is ready to easily tackle pumping and agitating even the deepest lagoons, pits, and slurry storage.

- 18" White Iron Bazooka Farmstar submersible pump
- 10-inch plumbing
- 42' boom reach
- Dual, rotating agitation nozzles provide agitation while pumping
- Gooseneck or bumper hitch trailer



Shown with 52' boom

FEATURES

HIGH FLOW AND INCREASED EFFICIENCY

The Outlaw is ready to increase your productivity.

- 10-inch plumbing increases flow and/or reduces power consumption.
- Pump Over 4,000 GPM: 577-684+ horsepower engine configurations are available to choose the power you need for your operation.
- The high-performance 18" white iron Bazooka Farmstar submersible pump features a heavy-duty bearing housing with no mechanical seal for easy maintenance.

INCREASED BOOM REACH AND MANEUVERABILITY

The 42' boom length perfectly fits manure lagoons, "hard to reach" confinement pits, and slurry storage tanks.

- Max. Depth: 21' below grade out 19' from the side of the trailer
- Max. Reach: 41' from side of trailer at ground level
- Max. Slurry Store Height: 20' 6"

The triple-section boom rotates 270° (180° to the left, 90° to the right), allowing you to set up in one location and pump out multiple pump-outs.

ELECTRIC PUMP BACKUP

Set up and take down without starting the engine. The 12V DC hydraulic pump will automatically operate the pig launcher, discharge gate valves, and outriggers when the engine is not running. The electric pump also provides backup hydraulic flow for the emergency operation of the boom.

42' OUTLAW FORCE-FEED TRAILER

SPECIFICATIONS

STANDARD

- Gross Weight: 25,000 lbs. (Not including fuel)
- Gooseneck Trailer Length: 31' 9" (Bumper hitch trailer available)
- Gooseneck Trailer Width: 103"
- Approximate Overall Trailer Height: 12'9" (153")
- Tongue Weight: Full- 2,000 lbs. | Empty- 800 lbs.
- Triple-Fold Boom
- Single, 500-Gallon Steel Fuel Tank w/ Baffle and Sump Area
- [2] 15,000 lbs. Tandem Leaf Spring Axles
- [4] 10-Bolt 22.5x13 -3 Offset Used Super Single Tires
- 12,000 lbs. Greaseable, Quick-Change Hubs, and Spindles
- Fenders
- DOT Trailer Lighting
- Rear Hitch Receiver Ready with Trailer Plug
- Rear Axle Electric Over Hydraulic Brakes
- Front Storage Basket Built into the Frame
- Integrated Rear Toolbox with USB Charging Port for Remote
- Discharge Plumbing, 10" Pig Launcher with Chained Cap, and Hydraulic Gate Valves
- Dual Agitation Nozzles with Individual Gate Valves

- [8] LED Flood Lights
- 360° Flood Light Halo [6] LED Flood Lights Included
- Electric Over Hydraulic Pump Backup
- 18" White Iron Bazooka Farmstar Submersible Pump
- Rear Mounted Hydraulic and Engine Controls
- 24" Stroke Front Hydraulic Downriggers
- 30" Rear Hydraulic Outriggers, Extending 60"

UPGRADES

- [4] 10-Bolt 22.5x13 -3 Offset New Super Singles
- [4] 550 Series 45-22.5 18-Ply Flotation Tires
- Discharge Plumbing with Pig Launcher and Hydraulic Gate valves (81022 Pumps)
- NEXUS Engine Control System | Includes 2 Digital Pressure Gauges, Antenna, Stand, and 1 Year Paid Subscription
- Manual Clutch with Hand Lever
- Hydraulic Clutch Controlled by NEXUS
- 8" Krohne Flowmeter, Display, and [2] 12' Cables
- Front Electric Over Hydraulic Bakes
- Wireless Boom Remote Control Transmitter
- Remote Control Charger [1] | Car 12V Micro USB
- Remote Control Charger [1] | Wall 110V Micro USB
- 5000 PSI Hydraulic Hook Up for Submersible

SUGGESTED PACKAGES FOR GPM

- 3500 GPM | 577 HP
- 4000 GPM | 660 HP or 684 HP
- 4500 GPM | 780 HP +



Shown with 52' boom

WWW.BAZOOKAFARMSTAR.COM