

# RENEGADE 2 AGITATION TRAILER

## POWERFUL AGITATION. UNMATCHED PUMPING.

The Renegade 2 agitation trailer is designed to maximize efficiency when agitating, transferring, filling tanks, or force-feeding from a liquid manure source. This upgraded agitation trailer is ready to change the game for your pumping operation with increased flow, longer boom lengths, and even more convenient features.

- Convenient, all-in-one agitation and pumping solution
- Increased productivity and efficiency
- Reduce time between fields
- Low maintenance design
- Safely travel roadways, bridges, and through towns



## FEATURES

### HIGH FLOW AND INCREASED EFFICIENCY

- The Renegade 2 comes standard with a 180 CC hydrostat motor which will reach a GPM of up to 4,000 when paired with a 250 HP or 310 HP engine and 18" Bazooka Farmstar submersible pump. When equipped with the upgraded hydrostat package, 4,500 GPM is possible.
- The high-performance 18" white iron Bazooka Farmstar submersible pump features a heavy-duty bearing housing with no mechanical seal for easy maintenance.
- 10-inch plumbing increases flow and/or reduces power consumption.

### INCREASED BOOM REACH AND MANEUVERABILITY

The 42' boom length perfectly fits manure lagoons, "hard to reach" confinement pits, and slurry storage tanks.

- Max. Depth: 21' below grade out 19' from the side of the trailer
- Max. Reach: 41' from side of trailer at ground level
- Max. Slurry Store Height: 20' 6"

The triple-section boom rotates 270° (180° to the left, 90° to the right), allowing you to set up in one location and pump out multiple pump-outs.

### INTEGRATED 12" DIAMETER LOAD STAND

The 12" diameter load stand increases your loading speed while reducing foaming. The boom remote can control the load stand for easy and precise placement of the fill pipe, and the tank fill remote fob can speed up the tank filling process by allowing operators to switch from agitation to fill mode without leaving the cab.

# RENEGADE 2 AGITATION TRAILER

## SPECIFICATIONS

### STANDARD

- Gross Weight: 20,000 lbs. (Not including fuel)  
Gooseneck Hitch Trailer Length: 31' 9" (381")
- Trailer Width: 103"
- Approximate Overall Trailer Height: 12'9" (153")
- Tongue Weight: Full- 2,000 lbs. | Empty- 800 lbs.
- 42' Triple Section Boom w/ Nickel-Plated Pins
- Low Mounted Discharge Plumbing
- 18" White Iron Bazooka Farmstar Submersible Pump
- [2] 3.5" Diameter Agitation Nozzles with Individual Gate Valve Control
- Rear Axle Electric Over Hydraulic Brakes
- 15,000 lbs. Tandem Leaf Spring Axles
- [4] 10-Bolt 22.5x13 -3 Offset Used Super Single Tires
- [4] 12,000 lbs. Greaseable, Quick-Change Hubs, and Spindles
- 250-Gallon Steel Fuel Tank w/ Baffle and Sump Area
- Integrated Rear Toolbox with USB Charging Port for Remote
- DOT Trailer Lighting
- [8] LED Flood Lights
- 360° Flood Light Halo [6] LED Flood Lights Included

- Built-In Front Storage Basket
- Rear Hitch Receiver Ready with Trailer Plug
- 10" Boom Plumbing
- Manual Agitation and Boom Controls
- Rear Mounted Hydraulic and Engine Controls
- 24" Stroke Front Hydraulic Downriggers
- 30" Rear Hydraulic Outriggers, Extending 60"
- Tec-10 Engine Control Package
- Electric Over Hydraulic Pump Backup

### UPGRADES

- [4] 10-Bolt 22.5x13 -3 Offset New Super Single Tires
- [4] Flotation Tires - 550 Series 45 - 22.5 18-Ply
- 12" Integrated Loadstand Boom
- Hydraulic Rear-Mounted Hose Reel | Holds 100' of 10" Lay Flat Hose
- Front Electric Over Hydraulic Bakes
- Wireless Remote Control Transmitter - Boom and Agitation Nozzle Rotation Function
- Remote Control FOB to Switch Between Fill and Agitation Functions
- [1] Remote Control Charger | Car 12V Micro USB
- [1] Remote Control Charger | Wall 110V Micro USB
- 5000 PSI Hydraulic Hook Up for Submersible

### LOAD STAND OPTION

- Length: 18'
- Max. Reach: 15'
- Max. Height: 16'5" From ground to bottom of rubber hose
- Trailer Weight: Increases 1,550 lbs.
- Tongue Weight: Increases 1,090 lbs.

