

STANDARD 3-POINT TOOLBAR WITHOUT SWING ARM



PRECISION INJECTION PAIRED WITH YOUR PREFERRED SWING ARM.

The Standard 3-Point Toolbar without Swing Arm utilizes the rugged design of our 3-Point Toolbar with the flexibility to use your preferred tractor-mounted swing arm. The Standard 3-Point Toolbar uses Phantom injection units to inject liquid manure and effectively lock nutrients in the ground.

- **Pair with tractor-mounted swing arm**
- **GPA Rates from 2,000 - 20,000+**
- **Compatible with Phantom Edge injection units**
- **Rigid toolbar design**

FEATURES

PRECISE INJECTION FOR HIGHER YIELDS AND REDUCED ODOR

The Phantom unit precisely injects liquid manure 4-6" into the ground using its 22" main coulter blade and a 17" single closure blade. This is the ideal nutrient depth to promote crop growth, and ultimately increase yields.

PAIR WITH TRACTOR-MOUNTED SWING ARM

The Standard 3-Point Toolbar without Swing Arm utilizes a hose connection from the flux manifold to connect to a tractor-mounted swing pipe.

ACCESSIBLE FLUX MANIFOLD

The flux manifold ensures consistent and precise manure flow distribution throughout the system. The flux manifold's hydraulic gate valve can be opened to clean out the manifold on the go without leaving the tractor cab, or if you are outside the cab, you can easily access and clean out the blockage.

STANDARD 3-POINT TOOLBAR WITHOUT SWING ARM

SPECIFICATIONS

STANDARD

- Toolbar widths and unit spacings available upon request
- Phantom units on 6° mounting plates
- 6" Flux Manifold
- DOT lighting
- Stainless steel knife gate valves
- 2.5" Bumblebee hoses
- Pig and main valve indicator lights
- Leg stands

UPGRADES

- Manifold clog indicator light
- 3" Bumblebee hose
- Phantom Edge injection unit

